

## AMENDMENTS TO THE CLAIMS

Please cancel claims 2, 10, 18, 22, 30, 38, 42, 50, 58, 62, 70 and 78. Please amend claims 1, 9, 17, 21, 29, 37, 41, 49, 57, 61, 69, and 77. This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of the Claims

## CLAIMS

What is claimed is:

- 1           1.     (Currently Amended) A locator for a wireless communication device that  
2     has a device identification, the locator can be coupled to an outlet box that is mounted to a  
3     wall and has a physical location, and coupled to a server that has a relational database that  
4     correlates the device identification with the physical location, comprising:  
5           a housing that is coupled to the outlet box;  
6           a transceiver that is coupled to said housing and wirelessly coupled to the wireless  
7     communication device to receive the device identification; and,  
8           a circuit that is coupled to said transceiver and contains a stored locator address  
9     that corresponds to the physical location of the outlet box, said circuit transmits said  
10    stored locator address and the device identification to the server, said circuit compares the  
11    device identification with a stored device identification and only transmits the device  
12    identification and said stored locator address if the device identification is different from  
13    said stored device identification.

1           2.     (Canceled)

1           3.     (Original) The locator of claim 1, wherein said circuit transmits the device  
2     identification and said stored locator address if a 9-1-1 call is generated from the wireless  
3     communication device.

1           4.     (Original) The locator of claim 1, wherein said circuit includes a processor  
2     and a memory.

1           5.     (Original) The locator of claim 1, wherein said transceiver includes an  
2     antennae.

1           6.     (Original) The locator of claim 1, further comprising an electrical  
2     connector attached to said housing and coupled to said circuit.

1           7.     (Original) The locator of claim 6, wherein said electrical connector is a  
2     RJ-45 device.

1           8.     (Original) The locator of claim 1, wherein said circuit retransmits wireless  
2     communication received from the wireless communication device.

1           9.     (Currently Amended) A locator for a wireless communication device that  
2     has a device identification, the locator can be coupled to an outlet box that is mounted to a  
3     wall and has a physical location, and coupled to a server that has a relational database that  
4     correlates the device identification with the physical location, comprising:

5           a housing that is coupled to the outlet box;

6           a transceiver that is coupled to said housing and wirelessly coupled to the wireless  
7     communication device to receive the device identification; and,

8           circuit means for transmitting a stored locator address and the device identification  
9     to the server, said stored locator address corresponds to the physical location of the outlet  
10    box, said circuit means compares the device identification with a stored device  
11    identification and only transmits the device identification and said stored locator address  
12    if the device identification is different from said stored device identification.

1           10.    (Canceled)

1           11.    (Original) The locator of claim 9, wherein said circuit means transmits the  
2     device identification and said stored locator address if a 9-1-1 call is generated from the  
3     wireless communication device.

1           12.    (Original) The locator of claim 9, wherein said circuit means includes a  
2     processor and a memory.

1           13.   (Original) The locator of claim 9, wherein said transceiver includes an  
2 antennae.

1           14.   (Original) The locator of claim 9, further comprising an electrical  
2 connector attached to said housing and coupled to said circuit.

1           15.   (Original) The locator of claim 14, wherein said electrical connector is a  
2 RJ-45 device.

1           16.   (Original) The locator of claim 9, wherein said circuit means retransmits  
2 wireless communication received from the wireless communication device.

1           17.   (Currently Amended) A method for locating a wireless communication  
2 device that has a device identification with a locator that can be coupled to an outlet box  
3 that is mounted to a wall and has a physical location, the locator being coupled to a server  
4 that has a relational database that correlates the device identification with the physical  
5 location, comprising:

6           connecting a locator to the outlet box;

7           transmitting a wireless communication to the locator from the wireless  
8 communication device, the wireless communication including the device identification;

9           and,

10           comparing the device identification with a stored device identification;

11 transmitting the device identification and a stored locator address from the locator  
12 to the server if the device identification does not match the stored identification device,  
13 the stored locator address corresponds to the physical address of the outlet box.

1 18. (Canceled)

1 19. (Original) The method of claim 17, wherein the device identification and  
2 stored locator address are transmitted in response to the wireless communication device  
3 transmitting a 9-1-1 call.

1 20. (Original) The method of claim 17, wherein the locator retransmits the  
2 wireless communication.

1 21. (Currently Amended) An outlet box that is mounted to a wall and has a  
2 physical location, a wireless communication device that has a device identification, the  
3 outlet box being coupled to a server that has a relational database that correlates the  
4 device identification with the physical location, comprising:

5 a housing;

6 a transceiver that is coupled to said housing and wirelessly coupled to the wireless  
7 communication device to receive the device identification; and,

8 a circuit that is coupled to said transceiver and contains a stored locator address  
9 that corresponds to the physical location of the outlet box, said circuit transmits said

10 stored locator address and the device identification to the server, said circuit compares the

11 device identification with a stored device identification and only transmits the device  
12 identification and said stored locator address if the device identification is different from  
13 said stored device identification.

1 22. (Canceled)

1 23. (Original) The outlet box of claim 22, wherein said circuit transmits the  
2 device identification and said stored locator address if a 9-1-1 call is generated from the  
3 wireless communication device.

1 24. (Original) The outlet box of claim 21, wherein said circuit includes a  
2 processor and a memory.

1 25. (Original) The outlet box of claim 21, wherein said transceiver includes an  
2 antennae.

1 26. (Original) The outlet box of claim 21, further comprising an electrical  
2 connector attached to said housing and coupled to said circuit.

1 27. (Original) The outlet box of claim 26, wherein said electrical connector is  
2 a RJ-45 device.

1           28.   (Original) The outlet box of claim 21, wherein said circuit retransmits  
2 wireless communication received from the wireless communication device.

1           29.   (Currently Amended) An outlet box that is mounted to a wall and has a  
2 physical location, a wireless communication device that was a device identification, the  
3 locator being coupled to a server that has a relational database that correlates the device  
4 identification with the physical location, comprising:

5           a housing;

6           a transceiver that is coupled to said housing and wirelessly coupled to the wireless  
7 communication device to receive the device identification; and,

8           circuit means for transmitting a stored locator address and the device identification  
9 to the server, said stored locator address corresponds to the physical location of the outlet  
10 box, said circuit means compares the device identification with a stored device  
11 identification and only transmits the device identification and said stored locator address  
12 if the device identification is different from said stored device identification.

1           30.   (Canceled)

1           31.   (Original) The outlet box of claim 29, wherein said circuit means transmits  
2 the device identification and said stored locator address if a 9-1-1 call is generated from  
3 the wireless communication device.

1           32.   (Original) The outlet box of claim 29, wherein said circuit means includes  
2 a processor and a memory.

1           33.   (Original) The outlet box of claim 29, wherein said transceiver includes an  
2 antennae.

1           34.   (Original) The outlet box of claim 29, further comprising an electrical  
2 connector attached to said housing and coupled to said circuit.

1           35.   (Original) The outlet box of claim 34, wherein said electrical connector is  
2 a RJ-45 device.

1           36.   (Original) The outlet box of claim 29, wherein said circuit retransmits  
2 wireless communication received from the wireless communication device.

1           37.   (Currently Amended) A method for locating a wireless communication  
2 device that has a device identification with an outlet box that is mounted to a wall and has  
3 a physical location, the outlet box being coupled to a server that has a relational database  
4 that correlates the device identification with the physical location, comprising:

5           transmitting a wireless communication to the outlet box from the wireless  
6 communication device, the wireless communication including the device identification;  
7 and,



8           comparing the device identification with a stored device identification;  
9           transmitting the device identification and a stored locator address from the outlet  
10   box to the server if the device identification does not match the stored device  
11   identification, the stored locator address corresponds to the physical address of the outlet  
12   box.

1           38.   (Canceled)

1           39.   (Original) The method of claim 37, wherein the device identification and  
2   stored locator address are transmitted in response to the wireless communication device  
3   transmitting a 9-1-1 call.

1           40.   (Original) The method of claim 37, wherein the outlet box retransmits the  
2   wireless communication.

1           41.   (Currently Amended) A locator system for a wireless communication  
2   device that has a device identification, the system includes a locator that can be coupled  
3   to an outlet box that is mounted to a wall and has a physical location, comprising:  
4           a location information server that contains a relational database, said relational  
5   database correlates the device identification with the physical location of the outlet box;  
6   and,  
7           a locator that is connected to the outlet box, said locator receives a wireless  
8   communication from the wireless communication device that includes the device

9 identification, said locator contains a stored locator address that corresponds to the  
10 physical location of the outlet box, and transmits said stored locator address and the  
11 device identification to said location information server, said locator compares the device  
12 identification with a stored device identification and only transmits the device  
13 identification and said stored locator address if the device identification is different from  
14 said stored device identification.

1 42. (Canceled)

1 43. (Original) The system of claim 41, wherein said locator transmits the  
2 device identification and said stored locator address if a 9-1-1 call is generated from the  
3 wireless communication device.

1 44. (Original) The system of claim 41, wherein said locator includes a  
2 processor and a memory.

1 45. (Original) The system of claim 41, wherein said locator includes an  
2 antennae.

1 46. (Original) The system of claim 41, wherein said locator includes an  
2 electrical connector.

1           47.   (Original) The system of claim 46, wherein said electrical connector is a  
2 RJ-45 device.

1           48.   (Original) The system of claim 41, wherein said locator retransmits  
2 wireless communication received from the wireless communication device.

1           49.   (Currently Amended) A locator system for a wireless communication  
2 device that has a device identification, the system includes a locator that can be coupled  
3 to an outlet box that is mounted to a wall and has a physical location, comprising:

4           a location information server that contains a relational database, said relational  
5 database correlates the device identification with the physical location of the outlet box;  
6 and,

7           locator means for receiving a wireless communication from the wireless  
8 communication device that includes the device identification, and transmitting a stored  
9 locator address and the device identification to said location information server, said  
10 stored locator address corresponds to the physical location of the outlet box, said locator  
11 means compares the device identification with a stored device identification and only  
12 transmits the device identification and said stored locator address if the device  
13 identification is different from said stored device identification.

1           50.   (Canceled)

1           51.   (Original) The system of claim 49, wherein said locator means transmits  
2 the device identification and said stored locator address if a 9-1-1 call is generated from  
3 the wireless communication device.

1           52.   (Original) The system of claim 49, wherein said locator means includes a  
2 processor and a memory.

1           53.   (Original) The system of claim 49, wherein said locator means includes an  
2 antennae.

1           54.   (Original) The system of claim 49, wherein said locator means includes an  
2 electrical connector.

1           55.   (Original) The system of claim 54, wherein said electrical connector is a  
2 RJ-45 device.

1           56.   (Original) The system of claim 49, wherein said locator means retransmits  
2 wireless communication received from the wireless communication device.

1           57.   (Currently Amended) A method for locating a wireless communication  
2 device that has a device identification with a locator that can be coupled to an outlet box  
3 that is mounted to a wall and has a physical location, the locator being coupled to a

4 location information server that has a relational database that correlates the device  
5 identification with the physical location, comprising:  
6 connecting a locator to the outlet box;  
7 comparing the device identification with a stored device identification;  
8 transmitting a wireless communication to the locator from the wireless  
9 communication device, the wireless communication including the device identification;  
10 transmitting the device identification and a stored locator address from the locator  
11 to the location information server if the device identification does not match the stored  
12 device identification, the stored locator address corresponds to the physical address of the  
13 outlet box; and,  
14 correlating the device identification with the physical location within the relational  
15 database.

1 58. (Canceled)

1 59. (Original) The method of claim 57, wherein the device identification and  
2 stored locator address are transmitted in response to the wireless communication device  
3 transmitting a 9-1-1 call.

1 60. (Original) The method of claim 57, wherein the locator retransmits the  
2 wireless communication.

1           61.   (Currently Amended) A locator system for a wireless communication  
2 device that has a device identification, the system includes an outlet box that is mounted  
3 to a wall and has a physical location, comprising:

4           a location information server that contains a relational database, said relational  
5 database correlates the device identification with the physical location of the outlet box;  
6 and,

7           an outlet box that receives a wireless communication from the wireless  
8 communication device that includes the device identification, said outlet box contains a  
9 stored locator address that corresponds to the physical location of said outlet box, and  
10 transmits said stored locator address and the device identification to said location  
11 information server, said outlet box compares the device identification with a stored device  
12 identification and only transmits the device identification and said stored locator address  
13 if the device identification is different from said stored device identification.

1           62.   (Canceled)

1           63.   (Original) The system of claim 61, wherein said outlet box transmits the  
2 device identification and said stored locator address if a 9-1-1 call is generated from the  
3 wireless communication device.

1           64.   (Original) The system of claim 61, wherein said outlet box includes a  
2 processor and a memory.

1           65.   (Original) The system of claim 61, wherein said outlet box includes an  
2 antennae.

1           66.   (Original) The system of claim 61, wherein said outlet box includes an  
2 electrical connector.

1           67.   (Original) The system of claim 66, wherein said electrical connector is a  
2 RJ-45 device.

1           68.   (Original) The system of claim 61, wherein said outlet box retransmits  
2 wireless communication received from the wireless communication device.

1           69.   (Currently Amended) A locator system for a wireless communication  
2 device that has a device identification, the system includes an outlet box that is mounted  
3 to a wall and has a physical location, comprising:

4           a location information server that contains a relational database, said relational  
5 database correlates the device identification with the physical location of the outlet box;  
6 and,

7           outlet box means for receiving a wireless communication from the wireless  
8 communication device that includes the device identification, and transmitting a stored  
9 locator address and the device identification to said location information server, said  
10 stored locator address corresponds to the physical location of the outlet box, said outlet

11 box means compares the device identification with a stored device identification and only  
12 transmits the device identification and said stored locator address if the device  
13 identification is different from said stored device identification.

1 70. (Canceled)

1 71. (Original) The system of claim 69, wherein said outlet box means  
2 transmits the device identification and said stored locator address if a 9-1-1 call is  
3 generated from the wireless communication device.

1 72. (Original) The system of claim 69, wherein said outlet box means includes  
2 a processor and a memory.

1 73. (Original) The system of claim 69, wherein said outlet box means includes  
2 an antennae.

1 74. (Original) The system of claim 69, wherein said outlet box means includes  
2 an electrical connector.

1 75. (Original) The system of claim 74, wherein said electrical connector is a  
2 RJ-45 device.



1           76. (Original) The system of claim 70, wherein said outlet box means  
2 retransmits wireless communication received from the wireless communication device.

1           77. (Currently Amended) A method for locating a wireless communication  
2 device that has a device identification with an outlet box that is mounted to a wall and has  
3 a physical location, the locator being coupled to a location information server that has a  
4 relational database that correlates the device identification with the physical location,  
5 comprising:

6           transmitting a wireless communication to the outlet box from the wireless  
7 communication device, the wireless communication including the device identification;  
8           comparing the device identification with a stored device identification;

9           transmitting the device identification and a stored locator address from the outlet  
10 box to the location information server if the device identification does not match the  
11 stored device identification, the stored locator address corresponds to the physical address  
12 of the outlet box; and,

13           correlating the device identification with the physical location within the relational  
14 database.

1           78. (Canceled)

1           79.   (Original) The method of claim 77, wherein the device identification and  
2   stored locator address are transmitted in response to the wireless communication device  
3   transmitting a 9-1-1 call.

1           80.   (Original) The method of claim 77, wherein the outlet box retransmits the  
2   wireless communication.